

81	82	83
		
Rocker switch 1 pole	Rocker switch 1 and 2 pole	Rocker switch 2 x 1 pole
20 (2) A 250V~ 1E4 T 125 16 (8) A 250V~ 1E4 T 125 10 (6) A 250V~ 5E4 T 125 10 (4) A 400V~ 1E4 T 125		
20 A 125V AC T 105 16 A 250V AC T 105 3/4 HP 125/250V AC T 105		
12 (10) A 250V~ 5E4 (T 85)		
125°C (105°C)		
ON/OFF, change over, change over center off. • NO, NC, change over momentary illuminated and non-illuminated. • Only for 82 Series: 1 pole versions with semi-independent lamp, center off momentary on one side. Only for 83 Series: 1 switch + 1 signal lamp.		
IP 40 (PVC cover available)		
 Tab terminals 6.3 x 0.8 mm Tab terminals 4.8 x 0.8 mm  Screw terminals only for 82 and 83		
0.7 to 3.5 mm 0.7 to 2.5 mm with PVC cover		
Illuminated Rockers  Standard  LED effect-lens Not illuminated Rockers  Standard  Bi-color Special version  Body with security frame Rocker shapes available  Flat  Soft		
30 x 11 mm	30 x 22 mm UK: 28,2 x 22,3 mm	30 x 22 mm UK: 28,2 x 22,3 mm
		
		